

# Button

## Wireless alarm button / smart button

### Tech specs

Classification	Addressed Radio Panic Button
Compatibility	Operates with <a href="#">hub Ajax</a> , and <a href="#">ReX</a> featuring OS Malevich 2.7.102 and later
False alarm prevention	Yes (in the Panic mode)
Number of buttons	1
Alarm transmission	Not longer than 0,15 sec Active from the first click (no need to wake it up)
Adjustable alarm types	Intrusion Fire Medical help Panic button Gas
Jeweller radio technology	Communication range with a hub – up to 1300 m in an open area Two-way communication channel Operating frequencies – 868.0–868.6 MHz Self-adjusting RF output power – up to 20 mW Block encryption based on AES algorithm Frequency hopping  <a href="#">Learn more about Jeweller &gt;</a>
Power supply	Battery: CR2032 battery Power supply voltage: 3 V Battery life – up to 5 years
Operating temperature range	From -10°C to +40°C
Permissible humidity	Up to 75%
Protection class	IP55
Size	47 x 35 x 13 mm
Weight	16 g
Warranty	Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty.  <a href="#">Learn more &gt;</a>
Complete set	Panic button

Pre-installed CR2032 battery

Double-sided tape

Quick Start Guide