

StreetSiren

Wireless siren with LED frame and piezoelectric buzzer. The device is designed for both outdoor and indoor installation.

- Protection against forgery
- Jamming detection
- Tamper against enclosure opening and accelerometer against detachment

Has IP54 protection class. Operates in temperatures from -25°C to +50°C.	Informs about alarms, delays, security mode changing and door openings.	Operates up to 5 years on a pre-installed battery. Can be supplied from the 12 V= backup power supply.
---	---	--

Operating principle

StreetSiren responds to alarms and tampers triggering by activating the buzzer and LED frame in less than a second. The tamper button triggers when the enclosure is opened or broken, and the accelerometer triggers when somebody's attempting to move or dismantle the siren.

Features

The buzzer can be set to generate sound from 85 to 113 dB for an adjustable period from 3 seconds to 3 minutes¹, or it can be completely silent and respond only with LED indication. StreetSiren's hermetically sealed body has been rated IP54 level of ingress protection.

Hassle-free installation and setup

Ready to operate straight out the box: the battery is already installed, and there is no need to disassemble the siren. It can be connected to the hub in the mobile or desktop app with one click. The mounting process takes just a few minutes with SmartBracket mounting panel.

¹ Alarm duration of 3 to 15 minutes is available only for sirens with firmware version 5.60.4.14 or higher. The function is available in the USA and Canada only when the siren is connected to the hub with NA X.X.X firmware version.