

HomeSiren Fibra

Wired siren with an external LED connector

<p>Compatibility</p>	<p>Compatible hub models</p> <p>Hub Hybrid (2G) Hub Hybrid (4G)</p>
<p>Communication</p>	<p>Fibra communication technology Proprietary wired communication technology. Fibra combines the reliability of wires with the freedom of radio connection.</p> <p>It features:</p> <ul style="list-style-type: none"> ● Two-way communication. ● Advanced anti-sabotage. ● Instant notifications. ● Remote configuration via the Ajax apps. <p>Line connection 4-core cable</p> <p>Fibra line length up to 2,000 m/up to 6,500 ft</p> <p>When using the U/UTP cat.5 twisted pair. Calculate the line length at the facility</p> <p>Encrypted communication</p>
<p>Key features</p>	<p>Alarm type acoustic and LED Buzzer and LED.</p> <p>Alarm volume from 81 to 105 dB at a distance of 1 m/3.3ft Adjusted by PRO or user with admin rights in the Ajax app.</p> <p>Alarm duration from 3 s to 3 min Adjusted by a PRO or user with admin rights in the Ajax app.</p> <p>Siren sound frequency 3.4 ± 0.5 kHz</p> <p>Additional LED connection 3 V An external LED works in parallel with the LED built into the siren and fully replicates its indication.</p> <p>Chime The siren makes a special sound to notify that the opening detectors are triggered when the system is disarmed.</p>

	<p>Events indication</p> <ul style="list-style-type: none"> • Alerts. • Entry/exit delays. • Security mode. • Security mode changing. • After-alarm indication.
Recomendations	The siren is designed for indoor use only. Recommended installation height is 2.5 m and higher.
Anti-sabotage protection	<p>Tampering alarm Alerts of attempts to detach the siren from the surface or remove the mounting panel.</p> <p>Protection against forgery Device authentication</p>
Power supply	<p>Fibra line power supply 5–30 V$\overline{=}$, up to 390 mW The siren is powered by the control panel.</p>
Enclosure	<p>Dimensions 90.5 × 90.5 × 33 mm/3.56" × 3.56" × 1.30"</p> <p>Weight 84 g/2.96 oz</p> <p>Operating temperature range from -10° C to +40° C/ from 14°F to 104°F</p> <p>Operating humidity up to 75%</p> <p>Protection class IP50</p>
Colours	<p>Black</p> <p>White</p>
Complete set	HomeSiren Fibra SmartBracket mounting panel Installation kit Quick Start Guide
Compliance with standards	Learn more
Warranty	24 months Learn more
User manual	Learn more