

StreetSiren Fibra

Wired siren for indoor and outdoor use

Compatibility	Compatible hub models Hub Hybrid (2G) Hub Hybrid (4G)
Communication	Fibra communication technology Proprietary wired communication technology. Fibra combines the reliability of wires with the freedom of radio connection. It features: <ul style="list-style-type: none">● Two-way communication.● Advanced anti-sabotage.● Instant notifications.● Remote configuration via the Ajax apps. Line connection 4-core cable Fibra line length up to 2,000 m/up to 6,500 ft When using the U/UTP cat.5 twisted pair. Calculate the line length at the facility Encrypted communication
Key features	Alarm type acoustic and LED Buzzer and LED frame. Alarm volume from 85 to 113 dB at a distance of 1 m/from 85 to 113 dB at a distance of 3.3 ft Adjusted by PRO or user with admin rights in the Ajax app. Alarm duration from 3 s to 3 min Adjusted by PRO or user with admin rights in the Ajax app. Siren sound frequency 3.5 ± 0.5 kHz Chime The siren makes a special sound to notify that the opening detectors are triggered when the system is disarmed.

	<p>Events indication</p> <ul style="list-style-type: none"> ● Alerts. ● Entry/exit delays. ● Security mode. ● Security mode changing. ● After-alarm indication.
Recommendations	The siren is designed for indoor and outdoor use. Recommended installation height is 2.5 m/6.6 ft and higher.
Anti-sabotage protection	<p>Tampering alarm Alerts of attempts to detach the siren from the surface or remove the mounting panel.</p> <p>Protection against forgery Device authentication</p>
Power supply	<p>Fibra line power supply 7–30 V=, up to 1.2 W The siren is powered by the control panel.</p>
Enclosure	<p>Dimensions 198.5 × 198.5 × 58 mm/7.81" × 7.81" × 2.28"</p> <p>Weight 575 g/20,28 oz</p> <p>Operating temperature range from –25° C to +60° C</p> <p>Operating humidity up to 95%</p> <p>Protection class IP54</p>
Colours	<p>Black</p> <p>White</p>
Complete set	StreetSiren Fibra SmartBracket mounting panel Installation kit Quick Start Guide
Compliance with standards	Learn more
Warranty	24 months Learn more
User manual	Learn more