




## Case D (430)

Casing for secure wired connection of Ajax devices.



3  
GRADE  
EN 50131




### Safe and quick connection with compatible devices

Install Ajax devices using Case. Choose the casing size with the required slot number depending on the number of products to be installed. Run cables and secure the devices in the simplest way. Quick and reliable fastening using durable latches and non-falling screws.



This is a case for installing one of the many possible device configurations. Due to the modular installation system, Case D (430) can house up to eight devices simultaneously. Compatible devices include Hub Hybrid (2G)<sup>1</sup>, Hub Hybrid (4G)<sup>1</sup>, LineSplit Fibra, LineProtect Fibra, MultiRelay Fibra, LineSupply (45 W) Fibra, LineSupply (75 W) Fibra, and 7–18 A·h batteries. There are alternative-sized casings available for different device combinations.



### Easy installation and maintenance

- Pre-installed tamper to detect the lid opening and alert of detachment of the casing from the surface
- Mounting holes placed at different angles and pre-installed spirit level to set the casing horizontally
- Perforated zones and fasteners for easy cable routing and management
- Multiple use – even after dismantling and changing device configuration
- Lid and device fixing in two positions – errors are excluded
- All mountings are included – PRO does not need to take an additional mount to the facility

Module Holder (type A) is used to install LineSplit Fibra, LineProtect Fibra, and MultiRelay Fibra modules, and Module Holder (type B) is used to install Hub Hybrid (2G)<sup>1</sup> and Hub Hybrid (4G)<sup>1</sup>.

#### Compatibility

Case D (430) is a casing for installing one of the many possible device configurations. This case can house up to eight devices simultaneously.

#### Compatible devices

Hub Hybrid (2G)<sup>1</sup>  
Hub Hybrid (4G)<sup>1</sup>  
LineSplit Fibra  
LineProtect Fibra  
MultiRelay Fibra  
LineSupply (45 W) Fibra  
LineSupply (75 W) Fibra  
7–18 A·h batteries  
(not included in the set)

#### Technical specifications

##### Color

white, black

##### Dimensions

430 × 400 × 133 mm

##### Weight

3,381 g

white Case D (430)

3,343 g

black Case D (430)

#### Installation

**Operating temperature range**  
from –10°C to +40°C

**Operating humidity**  
up to 75%

#### Complete set

Case D (430)  
Tamper board  
Holding stripe for a battery  
Module Holder (type A) – 4 pcs.  
Installation kit  
Quick start guide

<sup>1</sup> Installing the hub in Case D (430) does not meet the Grade (EN 50131) requirements.



For detailed information, scan the QR code or follow the link:

[ajax.systems/support/devices/case-fibra/](https://ajax.systems/support/devices/case-fibra/)

✉ support@ajax.systems

📍 @AjaxSystemsSupport\_Bot

🌐 ajax.systems