$\lambda J \lambda X$

Superior product line

HomeSiren S Jeweller

Wireless siren with external LED connector.



2 GRADE EN 50131 PD 6662 2017 INCERT SSF

What's new

Baseline HomeSiren Jeweller	Superior HomeSiren S Jeweller	
SmartBracket mounting panel without holding screw	SmartBracket mounting panel with holding screw	
Common battery	Enhanced battery	
Available for all PROs	Available only for accredited partners	

This is the device of the Superior product line. Superior products are advanced versions of Jeweller devices. This product line is developed for projects. Only accredited Ajax Systems partners can sell, install, and administer Superior products.



The siren responds to tamper and security system alarms in less than a second. It is loud enough to scare away intruders and attract the attention of neighbours.

The siren LED notifies that the system is armed or disarmed, and a sound signal indicates delay when entering/leaving. These are helpful features for users who control the security system with a keypad or key fob.



- Tamper alarm
- Device authentication to prevent spoofing
- Jamming detection ●
- Holding screw to secure the device on SmartBracket





- Up to 2,000 m of radio communication in an open space
- Data is encrypted throughout the transmission process
- Regular polling to display current device statuses
- Alarms of the system's devices
- Security status: armed/disarmed
- Door opening (Chime function)
- After-alarm indication



- Up to 5 years of battery life
- Low battery notifications
- Panasonic pre-installed battery

Compliance with standards



- Pairing with a hub via QR code
- Remote control and configuration in the app
- Effortless installation and replacement

Superior, Fibra, and Baseline product lines are mutually compatible. This opens up numerous possibilities for building systems of any configuration.

EN 50131-4 (Grade 2) PD 6662:2017 INCERT SSF

Compatibility

Hubs

Hub Plus, Hub 2 (2G), Hub 2 (4G), Hub 2 Plus, Hub Hybrid (2G), Hub Hybrid (4G)

Range extenders ReX, ReX 2 Communication with control panel

Jeweller communication technology

Frequency bands 868,0 — 868,6 MHz

Communication range up to 2,000 m In an open space Alerts

Alarms Acoustic

Delay When Entering/Leaving Acoustic

Security mode change Acoustic, LED

Security mode LED

Door opening (Chime function) Acoustic

After-alarm indication

Features

Types of notifications Acoustic, LED

Alarm volume from 81 to 105 dB at a distance of 1 m

Alarm duration from 3 s to 3 min

Piezoelectric buzzer frequency 3.5 ± 0.5 kHz

Additional LED connection Available, 3 V==

		LED	
Power supply	Installation	Enclosure	Complete set
Battery	Operating temperature range	Colour	HomeSiren S Jeweller
2 × CR123A	from -10°C to +40°C	white, black	SmartBracket panel with holding screw
Battery life	Operating humidity	Dimensions	2 × CR123A batteries
up to 5 years	up to 75%	75 × 76 × 27 mm	(pre-installed)
			Connector for third-party LED
	Protection class	Weight	Installation kit
	IP50	93 g	Quick start guide



For detailed information, scan the QR code or follow the link:

ajax.systems/support/devices/homesiren-s/

support@ajax.systems

- @AjaxSystemsSupport_Bot
- ajax.systems