

NVR

Network video recorder

Compatibility	Compatible hub models Hub Hub Plus Hub 2 (2G) Hub 2 (4G) Hub 2 Plus Hub Hybrid (2G) Hub Hybrid (4G)
Videostream	NVR models 8-channel 16-channel With up to 4K resolution (25/30 FPS). IP cameras <ul style="list-style-type: none">• ONVIF (Profile S/T)• RTSP Storage hard drive with a capacity of up to 16 TB (SATA connectivity, 3.5" size) HDD not included. Decoding formats H.265 H.264 Bandwidth up to 100 Mbps
Recommendations	The device operating voltage is 110–240 V~. NVR is designed for indoor installation only.
Communication channels	Ethernet up to 100 Mbps Bluetooth BLE frequency band: 2.400–2.4835 GHz To set up an Ethernet connection. Radio signal power 2.5 mW (100 mW limit)
Key features	Motion detection NVR has built-in software to detect the motion in the frame. Possible to switch between image analysis by NVR or camera algorithms. In-app video management system

	<ul style="list-style-type: none"> • Videowall that combines images from all connected cameras. • Event filters. • Timeline with smooth preview. <p>Visual verification of Ajax alarms NVR allows setting up a scenario in which Ajax detectors trigger specific cameras to start recording. This results straight in mobile and desktop (monitoring) apps.</p> <p>Privacy Access rights distribution for users in mobile apps and for monitoring operators in PRO Desktop.</p>
Power supply	<p>Main 110–240 V~, 50/60 Hz, 0.6 A Up to 24 W of mains power consumption.</p> <p>Backup CR2032 battery, 3 V Only to power the system clock.</p>
Anti-sabotage	<p>Tamper alarm Notifications about attempts to detach the device from the surface or remove it from the mounting panel.</p>
Enclosure	<p>Dimensions 251 × 251 × 51 mm/9.88" × 9.88" × 2.01"</p> <p>Weight 700 g/24.69 oz Without a hard drive.</p> <p>Operating temperature range from 0°C to +40°C/from 32°F to 104°F</p> <p>Operating humidity up to 75%</p> <p>Protection class IP20</p>
Colours	<p>Black White</p>
Complete set	<p>NVR SmartBracket mounting panel Power cable Ethernet cable Installation kit Quick Start Guide</p>
Warranty	<p>24 months</p>

