## Ajax DomeCam Mini

Wired IP camera

0 17.77	
Compatibility	Control panels
	Hub
	Hub Plus
	Hub 2 (2G)
	Hub 2 (4G)
	Hub 2 Plus
	Hub Hybrid (2G)
	Hub Hybrid (4G)
	Video recorders
	NVR
Models	5 Mp/2.8 mm
	<ul> <li>Resolution up to 2880 × 1620 px</li> </ul>
	Frame rate up to 25 FPS
	<ul> <li>Viewing angle from 100° to 110°</li> </ul>
	5 Mp/4 mm
	- I
	<ul> <li>Resolution up to 2880 × 1620 px</li> <li>Frame rate up to 25 FPS</li> </ul>
	<ul> <li>Viewing angle from 75° to 85°</li> </ul>
	viewing ungle nom to to co
	8 Mp/2.8 mm
	<ul> <li>Resolution up to 3840 × 2160 px</li> </ul>
	<ul> <li>Frame rate up to 20 FPS</li> </ul>
	<ul> <li>Viewing angle from 100° to 110°</li> </ul>
	8 Mp/4 mm
	Resolution up to 3840 × 2160 px
	Frame rate up to 20 FPS
	<ul> <li>Viewing angle from 75° to 85°</li> </ul>
Videostream	Video protocol
Videosticam	JetSparrow
	Fast and encrypted peer-to-peer video protocol
	developed by Ajax Systems.
	acresoped by right eyerenie.
	Storage
	NVR
	Hard drive with a capacity of up to 16 TB (SATA
	connectivity, 3.5" size). Memory storage device
	not included.
	microSD
	Up to 256 GB. Memory storage device not
	included.
	Video codec
	H.265
	H.264

	Dynamic ranges True WDR
Communication channel	Ethernet up to 100 Mbps
Key features	Motion detection The camera has software to detect motion in the frame.
	Object detection using AI  Humans. Pets. Vehicles.
	Smart IR illumination up to 15 m Automatic adjustment of intensity in real time to avoid overexposure. This allows you to see objects that are far away or too close to the camera in low light conditions.
	Visual verification of Ajax alarms The system allows you to set up a scenario when Ajax detectors activate selected cameras to start recording. The result is immediately sent to the mobile or desktop monitoring app.
	Microphone With the corresponding settings, the camera records sound at the object.
	Audio codec G711-ULAW G711-ALAW G726 G722
Power supply	Power supply unit 12 V= ± 20%, 1 A Up to 15 W of mains power consumption.
	Ethernet port PoE Standard 802.3at
Sabotage protection	mTLS Encrypted connection for data protection.
	Authentication via Cloud Without local access rights.

	Secure Boot Protection against firmware spoofing.  OTA signature verification Secure automatic firmware update.  Privacy Access rights distribution for users in mobile apps and for monitoring operators in PRO Desktop.
Enclosure	Dimensions 113 × 60 mm 4.45" × 2.36"  Weight 360 g 12.70 oz  Operating temperature range from -30 °C to +60 °C f r om -22 °F to 140 °F  Operating humidity up to 90%  Protection class IP65
Colours	Black White
Complete set	DomeCam Mini Installation template Installation kit Quick start guide
Warranty	24 months